



SPECIFICATION

Page 3, lines 4 – 7, please amend as follows:

FIG. 5 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention; and

FIG. 6 is another perspective view illustrating the L.E.D. emergency lamp of FIG. 5, constructed in accordance with the present invention;

FIG. 7 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, with an L.E.D. light adjustable and angled;

FIG. 8 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, with custom electronic modules sized and shaped for being received the battery compartment;

FIG. 9 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, with a Global Positioning Satellite (GPS);

FIG. 10 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, the housing edge is attachable in a folded down storage position latchable in a ninety (90°) degrees position;

FIG. 11 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, the housing edge is attachable in a folded down storage position latchable in a ninety (90°) degrees position; and

FIG. 12 is a perspective view illustrating the L.E.D. emergency lamp, constructed in accordance with the present invention, the housing edge is attachable in a folded down storage position latchable in a ninety (90°) degrees position.